



printhead cleaner built in your ribbon.

- Built right into your thermal transfer ribbons
- Preventative maintenance
- Fast and easy to use
- Maintains excellent print quality
- Prolongs printhead life
- Minimizes costly downtime



# Wax/Resin

## Technical Specifications

Color Code Tab.....	Teal
Maximum Print Speed .....	8 IPS
Film Thickness.....	4.5 Microns
Total Ribbon Thickness.....	8.4 Microns
Transmission Density .....	2.6
	MacBeth Scale
Ink Melting Point.....	65°C/149°F

## Sample PM308 Ribbons

Part # CES11027 - 110mm x 50m - CSI  
 Part # CES11026 - 110mm x 50m - CSO

# PM308

## Premium Wax/Resin



### Outstanding Versatility and Print Quality

#### Benefits

- Perform on a broad range of premium applications
- Prints on wide range of substrates including coated papers and smooth synthetic films.
- Excellent durability
- Stands up to rough handling, abrasion or moderate solvents
- Specially formulated backcoat protects the printhead

#### Recommended Stock

Coated paper (matte, semi gloss, high gloss)	Polypropylene
Polyolefin	Polyethylene
Polyester	



What you need to know to quote ribbon business.

### Thermal Transfer Ribbon STORAGE CONDITIONS

For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing IIMAK thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.

First in service. Impressions that last.<sup>SM</sup>



310 Commerce Drive  
 Amherst, NY 14228  
 Call toll-free: **888.464.4625**  
 Fax toll-free: **888.329.0260**

Order On-line: [www.iimak.com](http://www.iimak.com)  
 Phone: **716.691.6333**  
 Fax: **716.691.3395**  
 Email: [salesinfo@iimak.com](mailto:salesinfo@iimak.com)